

BULLETIN



KRALOY®
The Fitting Choice

Features and Benefits:

- Retrofit Option
- Corrosion Resistant
- Dimmable down to 5%
- Nema 4X and IP66 Rated
- 50,000 + hours of life
- Lumen output of 1575 lm
- LPF-LED's durable design is rated for hazardous use

Technical Specifications:

| | |
|---------------------------------|----------------|
| Lumen Output | 1575 lm |
| Input Voltage | 120 VAC |
| Frequency | 60 Hz |
| Nominal Power | 15 W |
| Colour Temperature | 5000 K |
| CRI | > 80 |
| Power Factor | 0.98 |
| Total Harmonic Distortion | 10.5% |
| Operating Temperature | -40°C to 40°C |
| Dimmability Range | Down to 5% |
| Rated Life | > 50,000 Hours |
| Warranty | 5 Years |

SCEPTALIGHT™ LED Nonmetallic Light Fixtures

Kraloy® Sceptalight LEDs offer significant energy savings and can last beyond 50,000 hours without a single need for maintenance. Sceptalight's thermoplastic construction offers outstanding corrosion and chemical resistance, making it a preferred choice wherever a lighting fixture is required to withstand exposure to chemicals, fluids, or harsh physical conditions. Certified and tested for use in indoor, outdoor, wet locations, wash down and corrosive environments, Sceptalight LEDs are certified to the latest LED light fixture standards and are NEMA 4X approved.

Ceiling Mount with Frosted Polycarbonate Globe (15W LED)

| Description | Part Number | Product Code | Standards |
|------------------------------|----------------|--------------|---------------------------------|
| Retrofit Light Engine | LLED-15-V2 | 277120 | CSA C22.2 250, UL 1598C |
| LPF Heavy Duty Light Fixture | LPF-LED-V2-HAZ | 277121 | CSA C22.2 250, UL 1598C, UL 844 |
| LPF Utility Light Fixture | LPF-LED-V2 | 277122 | CSA C22.2 250, UL 1598C |



RETRIFIT OPTION

Sceptalight LEDs can easily retrofit onto existing installations for increased energy savings.

DIMMABLE

Lights are dimmable down to 5% for maximum control of the lighting environment.

NEMA 4X AND IP66 RATED

Approved for wet locations, wash down and corrosive environments.

CORROSION RESISTANT

Heat sink is coated with a durable e-coat layer that prevents corrosion.

HEAT DISSIPATION

Specially designed heat sink ensures long life and optimum performance for over 50,000 hrs.

ENERGY EFFICIENT

1,575 lumens of light output is produced with only 15 Watts of electricity.

POLYCARBONATE GLOBE

Impact and weather resistant for tough environments.

Contact us: Toll free: (800) 265-1815 | kraloyfittings.com